Loewe AirSpeaker

Delivery contents
AirSpeaker
W 24.0 / H 12.9 / PD 24.0

Technical information
Loewe AirSpeaker

General	
Principle	2-way bass reflex, active
Nominal / music power (sine)	4 x 20 W
Frequency range	45 Hz – 20 kHz; ± 3 dB
Power supply unit	100 V – 240 V AC
Power consumption (nominal)	19 W
Power consumption (network stand-by)	4 W
Power consumption (stand-by)	< 0,5 W
Operation	
Operation (on device)	4 buttons: volume ±, source selection, On/Off
Remote control	o
Operation (WLAN)	remote control via iPod, iPhone, iPad
Configuration / Settings	browser interface
Features	
Power amps	Total output: 80 W 4 digital amplifiers (Class D) for analogue port connection or digital signal processing (iPhone, iPod, iPad)
Ports (analogue)	3.5 mm stereo jack
Ports (digital)	USB[1] (for iPod, iPhone, iPad only)
Network access	LAN (RJ45), WLAN (802.11 b.g)
Protocols	Apple AirPlay
Stand-by switch	●
Acoustic pressure (average)	90 dB / 0,5 m
Speaker complement	2 x 100mm cone speakers, 2 x 18mm tweeters
Miscellaneous	
Weight (approx.) in kg	6.0

Housing
Colours

	Model	Article no.	EAN Code
Black	AirSpeaker	51205L00	4011880135276
Silver	AirSpeaker	51205B00	4011880134538

Insets
Colours and materials

Metallised Chrome

Chrome Ribbed

Chrome Micro

Aluminium Silver

High Gloss Black

Ebony

Light Oak

individual colour preference on request

Technical features

Dimensions in cm: W = width, H = height, PD = product depth
● = included/installed o = upgradeable/optional
[1] USB port compatible with devices of max. 1A.

LOEWE.